

VMC 1200





ELECTRIC CLASS 3 TRUCK

The VMC 1200 from Vicinity Motor Corp. is a fully electric, class 3 truck. It excels in urban environments with it's ultra quiet operation and balance of range and payload. Typical applications include delivery truck, dump truck and work truck.

Powered by cutting edge Li-ion battery technology, the VMC 1200 can travel up to 241 kms (150 miles) on a single charge.

Designed by Vicinity Motor Corp. using our proven EV technology, the VMC 1200 is helping the transportation industry reduce costs, eliminate carbon emissions, and run a more efficient fleet.

Length6 m/ 20 ftWidth1.90 m/ 75 inHeight2.84 m/ 9.33 ftGVWR5000.0 kg/ 11,000 lbs

Payload Approx. 2495 kg/ 5,500 lbs

(cab/chassis only)

Tires 225 x 16
Suspension Leaf Spring
Brakes Hydraulic
Battery Li-ion 92.5kWh

5 Year Warranty

Charge Level 2 | 5-7 hrs

Level 3 | 2.5 hrs CCS1 Combo Plug

Motor 120kW (160 HP)

Range Up to 241 kms (150 miles) std.

Phone: (604) 607-4000

Email: sales@vicinitymotor.com



3168 262nd Street, Aldergrove B.C. Canada V4W 2Z6 Phone: 604-607-4000 | Fax: 604-607-4004 www. https://vmctrucks.com/

VMC 1200 Specifications

| Type | Fully Electric |
|-----------------|--------------------------|
| Model Year | 2023 |
| Style | Cabover |
| Class | 3 |
| Drive | 4 x 2 |
| Range | Up to 241 km (150 miles) |
| Max Speed | 100 km/h (62 m/h) |
| Gradeability | 26% |
| | |
| Drivetrain | |
| Motor | Permanent Magnet |
| | Synchronous Motor |
| Motor – cooling | Liquid |
| Power – rated | 55 kW (74 hp) |
| Power – peak | 120 kW (160 hp) |
| Torque – rated | 200 Nm (147 ft lbs) |
| Torque - peak | 380 Nm (280 ft lbs) |
| Transmission | 2 speed |
| Rear axle ratio | 6.167 |
| | |
| Weights | |
| GVWR | 5,000 kg (11,000 lbs) |
| Curb* | ~2,495 kg (5,500 lbs) |
| GAWR - Front | 2,000 kg (4,400 lbs) |
| GAWR – Rear | 3,500 kg (7,700 lbs) |
| | |
| Suspension | |
| Front | Solid axle - Leaf spring |
| Rear | Solid axle - Leaf spring |

^{*}Does not include body (flat bed, drybox, dump, etc). Curb weight increased by weight of body when equipped.

| High Voltage System | |
|---------------------|---------------------------------|
| Voltage | 525 V |
| Battery Capacity | 92.5 kWh |
| Battery Cooling | Air |
| Charging | CCS1 combo – up to level III |
| Low Voltage System | |
| Voltage | 12 V |
| DC – DC Converter | 120 amps |
| Brakes | |
| Туре | Hydraulic |
| Front | Disk |
| Rear | Drum |
| Wheels & Tires | |
| Tire Size | 225/75R16 LT or 215/75R16 LT |
| Wheel size | 6" x 16" |
| Wheel type | Painted steel |
| Interior | |
| Seats | Cloth |
| Seating | 3 |
| Driver's Seat | Bucket |
| Passenger Seats | Bench |
| Flooring | Vinyl |
| Convenience | |
| | |